

Information Technique

DIMENSIONS DES BOULONS, VIS, TIRANTS

A utiliser pour assemblage de brides normalisées

B : boulon V : vis T : tirant.


∅	15	20	25	32	40	50	65	80	100	125	150	200	250	300
Robinetterie à brides, tous modèles														
PN 10	8B 12/50	8B 12/50	8B 12/50	8B 16/50	8B 16/60	8B 16/60	8B 16/60	16B 16/60	16B 16/60	16B 16/70	16B 20/70	16B 20/70	24B 20/80	24B 20/80
PN 16	8B 12/50	8B 12/50	8B 12/50	8B 16/50	8B 16/60	8B 16/60	8B 16/60	16B 16/60	16B 16/60	16B 16/70	16B 20/70	24B 20/80	24B 24/90	24B 24/90
PN 25	8B 12/50	8B 12/50	8B 12/50	8B 16/60	8B 16/60	8B 16/60	16B 16/70	16B 16/70	16B 20/70	16B 24/80	16B 24/80	24B 24/90	24B 27/100	24B 27/100
PN 40	8B 12/50	8B 12/50	8B 12/50	8B 16/60	8B 16/60	8B 16/60	16B 16/70	16B 16/70	16B 20/70	16B 24/80	16B 24/80	24B 27/100	24B 30/120	32B 30/120
Vannes 8600 - 8620 - 8700 - 88														
PN 10	-	-	-	4T 16/100	4T 16/100	4T 16/110	4T 16/120	8T 16/120	8T 16/130	8T 16/140	8T 20/150	8T 20/160	12T 20/160	12T 30/170
PN 16	-	-	-	4T 16/100	4T 16/100	4T 16/110	4T 16/120	8T 16/120	8T 16/130	8T 16/140	8T 20/150	12T 20/160	12T 24/160	12T 24/170
Vannes 8601														
PN 10	-	-	-	-	-	8V 16/35	8V 16/40	16V 16/40	16V 16/45	16V 16/45	16V 20/45	16V 20/50	24V 20/55	24V 20/60
PN 16	-	-	-	-	-	8V 16/35	8V 16/40	16V 16/40	16V 16/45	16V 16/45	16V 20/45	-	-	-
Clapets 210														
PN 10	-	-	-	-	-	4B 16/70	4B 16/70	8T 16/110	8T 16/110	8T 16/110	8T 20/140	8T 20/140	12T 20/160	-
PN 16	-	-	-	-	-	4B 16/70	4B 16/70	8T 16/110	8T 16/110	8T 16/110	8T 20/140	8T 20/140	12T 20/160	-
Clapets 211														
PN 10	-	-	-	-	-	4T 16/130	4T 16/130	8T 16/140	8T 16/140	8T 16/150	8T 20/170	8T 20/190	12T 20/190	-
PN 16	-	-	-	-	-	4T 16/130	4T 16/130	8T 16/140	8T 16/140	8T 16/150	8T 20/170	12T 20/190	12T 24/190	-

ÉCARTEMENTS FAF SELON DIN

∅	15	20	25	32	40	50	65	80	100	125	150	200	250	300
DIN 3202/F1 - NFE 29350	130	150	160	180	200	230	290	310	350	400	480	600	730	850
DIN 3202/F4					140	150	170	180	190	200	210	230	250	270
DIN 3202/F5					240	250	270	280	300	325	350	400	450	500
DIN 3202/F7						250	290	310	350	400	450	550	650	750
DIN 558-1 PN 16					180	200	240	260	300	350	400	500	600	
DIN 558-1 PN 40					200	230	290	310	350	400	480	600	750	830

LONGUEUR DES MANCHETTES D'ÉCARTEMENT

∅		40	50	65	80	100	125	150	200	250	300
PN 10	D	150	165	185	200	220	250	285	340	395	445
PN 16	D	150	165	185	200	220	250	285	340	405	460
Modèle 8300											
Pour L	L	136	142	154	160	172	186	200	228	255	285
ISO PN 10	E	102	99	108	114	120	130	144	168	187	207
Fig 110.112											
Modèle 8302											
Pour L	L	140	150	170	180	190	200	210	230	250	270
ISO PN 10	E	106	107	124	134	138	144	154	170	182	192
Fig 106.107											



la robinetterie industrielle